



CLADDING

ITEM	PROFILE (min)	FINISH	COLOUR
ROOF	TRIMDEK 0.35 BMT	CB	SM
WALLS	MULTICLAD 0.35 BMT	CB	SM
CORNERS	-	CB	SM
BARGE	-	CB	SM
GUTTER	SHEERLINE	CB	SM
DOWNPIPE	100x50	CB	SM

0.35bmt=0.40tct; 0.42bmt=0.47tct; 0.48bmt=0.53tct

ACCESSORY SCHEDULE & LEGEND

QTY	MARK	DESCRIPTION
1	OO1	Roller Door opening, 2100 high x 5000 wide. Roller Door must be fitted, refer to the NCC for door compliance.
1	KFO1	2100H x 1800W Framed Opening. Door must be fitted

ARCHITECTURAL DRAWING ONLY, NOT FOR CONSTRUCTION USE

WIND DESIGN

IMPORTANCE LEVEL	REGION	TERRAIN	Ms
2	A	2.5	1.0

CLIENT
Craig Diessel

SITE
TBA
BOLTON POINT NSW 2283

BUILDING
SUNDOWN SUPER
6120 SPAN x 2400 EAVE x 9150 LONG

TITLE
GENERAL ARRANGEMENT

SCALE A4 SHEET 1:125	DRAWING NUMBER NEWC4-4614	REV A	PAGE 1/1
-------------------------	-------------------------------------	-----------------	--------------------